

MDF Woodgrip

High performance synthetic resin adhesive.

USES

Specially formulated to provide good adhesion to medium density fibreboard.

ADVANTAGES

- Easy to use
- Ideal for medium density fibreboard (Craftwood)
- Can be applied by gun, squeeze bottle or glue spreader.

PROPERTIES

Appearance	An apricot syrupy liquid.
Viscosity	1500 - 3000 CPS 4/20/25
Solids	Approx. 53%
Specific Gravity	Approx. 1.06
Initial Tack	Medium - develops fast tack.
Set Speed	Fast.

APPLICATION INSTRUCTIONS

Surfaces to be bonded should be clean and dry and free of grease and oil. It is recommended that light sanding be done before gluing. Joints to be bonded should be close fitting. Timber moisture content should be in the range of 7 - 10%.

Adhesive may be applied by brush, roller or squeeze bottle. When practical, apply to both surfaces of the joint.

Recommended spread rate is 3 - 5 M² of glue line per litre.

STORAGE

18 months if stored in original containers in a cool dry place.

PACKAGING

Squeeze bottle	500 ml
Jerry Type	4L, 20L

PRECAUTIONS - HEALTH AND SAFETY

MDF Woodgrip maybe an eye irritant. Inhalation of spray mist may cause irritation to the respiratory tract. As with any chemical, ingestion, inhalation and prolonged or repeated skin contact should be avoided by good occupational work practice.

NOTE

Material safety data sheets for these and all AFTEK Products are available on request. Read the MSDS and product label carefully before using.

All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

MARKETING SERVICES

THOMSON WHITE AUST P/L
250 Princes Hwy Dandenong Vic 3175
Tel: (03) 9791 8211
Fax: (03) 9791 8644
Email: ask@thomsonwhite.com.au