

Floorseal A

Acrylic resin based floor sealer

DESCRIPTION

Acrylic resin floor sealer for concrete to provide a dust proof and more easily cleaned work environment. Ideal for warehouses, car parks and industrial applications.

ADVANTAGES

- Resistance to liquid penetration
- Economical
- Easy application
- Single component
- Easy maintenance

TYPICAL PROPERTIES

Specific Gravity @ 20°C	0.98
Recoat time @ 20°C	4 Hours
Traffic Time	18 Hours

APPLICATION INSTRUCTIONS

Preparation

All surfaces to be treated must be free of oil, grease or other contamination which may inhibit penetration. Any loose concrete should be removed and repaired prior to treatment. Floorseal A may be applied to concrete which has been treated with Chlorcure.

Mixing

Floorseal A is suitable for application straight out of the container without prior mixing,

Application

Pour the Floorseal A in to the roller tray and use a roller to apply the Floorseal A at the rate of 6 - 8 m² per litre. Larger areas may be sprayed at the same application rate. Ensure an even finish by recoating

areas that appear to be porous. Apply a second coat of Floorseal A in the same way as the first coat. Coverage will be 8 - 10 m² per litre due to the reduced porosity of the surface. Take care to avoid pooling of Floorseal A on the surface.

CURING

Floorseal A is suitable for pedestrian traffic and over coating after 18 hours.

CLEAN UP

Clean all equipment with solvent immediately after use.

ESTIMATING

Packaging

Floorseal A is supplied in 20 and 200 Litre metal drums.

Approximate Material Usage

First Coat	4 - 6 m ² per litre
Second Coat	8 - 10 m ² per litre

STORAGE

Floorseal A is a solvent based product which must be stored in the original unopened containers.

PRECAUTIONS

Where temperatures less than 5°C or greater than 35°C are encountered, contact our Technical Staff for specific advice.

Floorseal A is solvent based. Protective gloves, goggles and clothing should be worn. Remove any splashes from metal, glass, tiles, etc. immediately using clean solvent.

MARKETING SERVICES

THOMSON WHITE AUST P/L
250 Princes Hwy Dandenong Vic 3175
Tel: (03) 9791 8211
Fax: (03) 9791 8644
Email: ask@thomsonwhite.com.au

FLOORSEAL A

NOTE

Material safety data sheets for these and all Aftek products are available on request. Read the MSDS and product label carefully before using.

All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

ALLIED PRODUCTS

Aftek manufactures a broad range of construction products including:

Grouts

Coatings

Admixtures

Adhesives

Sealants

Floor Toppings

Floor Levelling Compounds

Concrete Repair