

Floorseal CR

Protective floor coating based on chlorinated rubber

DESCRIPTION

Floorseal CR is a chlorinated rubber based floor coating for concrete floors which is easily applied and maintained, and provides a dust proof and decorative finish.

ADVANTAGES

- Easy to recoat
- Economical
- Easy application
- Excellent adhesion
- Low maintenance

TYPICAL PROPERTIES

Recoat time @ 20°C		6 Hours
Traffic Time	Pedestrian	24 hours
	Vehicle	48 hours
Colours	Clear and Grey. Other colours to order in sufficient quantity.	
Flash Point		28°C

APPLICATION INSTRUCTIONS

Preparation

All contacted surfaces must be free of oil, grease or other contamination which may inhibit bond. Any loose concrete should be removed and repaired to provide a solid foundation.

Mixing

Floorseal CR is suitable for mixing using a drill and suitable paddle, or spatula. Mix for 1 to 2 minutes to ensure an even colour.

Application

Apply the Floorseal CR by brush, roller or spray at the rate of 6 - 8 m² per litre in an even pattern over the floor.

Apply the second coat of Floorseal CR in the same way as the first coat. Coverage will be 8 - 10 m² per litre due to the reduced porosity of the surface.

Take care not to leave an excess of Floorseal CR on the surface.

CURING

Floorseal CR is suitable for overcoating after 6 hours, and pedestrian traffic after 24 hours.

CLEAN UP

Clean all equipment with xylene immediately after use.

ESTIMATING

Packaging

Floorseal CR is supplied in 20 Litre pails.

Material Usage

First Coat	6 - 8 m ² per litre
Second Coat	8 - 10 m ² per litre.

STORAGE

Floorseal CR is a solvent based product which must be stored in the original unopened containers.

PRECAUTIONS

Where temperatures less than 5°C or greater than 35°C are encountered, contact our Technical Staff for specific advice.

Floorseal CR is non toxic, but it is solvent based. Any contact with eyes or skin should be washed off with soap and clean water. Do NOT use solvent. Protective gloves, goggles and clothing should be worn. Repeated contact with solvent based products can cause sensitization in some people handling this type of product.

MARKETING SERVICES

THOMSON WHITE AUST P/L
250 Princes Hwy Dandenong Vic 3175
Tel: (03) 9791 8211
Fax: (03) 9791 8644
Email: ask@thomsonwhite.com.au

FLOORSEAL CR

PRECAUTIONS (cont)

Where this occurs seek medical advice before continuing use.

NOTE

Material safety data sheets for these and all Aftek products are available on request. Read the MSDS and product label carefully before using.

All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

Fire

Floorseal CR is highly flammable. Do not smoke during application. Keep away from naked flames.

Chemical Resistance

Do not use in applications involving contact with vegetable oils, some synthetic oils and concentrated chemicals without testing an applied sample.

ALLIED PRODUCTS

Aftek manufactures a broad range of construction products including.

Grouts

Coatings

Admixtures

Adhesives

Sealants

Floor Toppings

Floor Levelling Compounds

Concrete Repair