

# Stripform

## Oil based form release agent

### DESCRIPTION

Stripform is an oil based form release agent specifically formulated for application to timber and steel formwork.

### ADVANTAGES

- Economical
- Clean Release
- Solvent Free
- Easy application

### Typical Properties

Specific Gravity@ 20°C 0.95 gm/ml

### APPLICATION INSTRUCTIONS

#### PREPARATION

All formwork surfaces must be free of mortar, grease or other contamination which may affect the concrete appearance.

#### Application

Stripform is suitable for use straight out of the drum without mixing. Apply the Stripform to the formwork using a brush, roller or spray at the rate of 8 - 10 m<sup>2</sup> per litre. Avoid an excess of Stripform on the surface to prevent a dusty or stained finish on the concrete.

#### Curing

The application of Curecon WB as a curing membrane will reduce premature drying and shrinkage.

#### CLEAN UP

Clean all equipment immediately after use. Coat tools and forms with Stripform before storage to protect against corrosion.

### ESTIMATING

#### Packaging

Stripform is supplied in 20 litre and 200 litre drums.

#### Estimating Data

A 20 litre drum of Stripform will cover approximately 180 m<sup>2</sup> at an average rate of 9 m<sup>2</sup> per litre.

#### STORAGE

Stripform is an oil based product which must stored in a dry area off the ground.

#### PRECAUTIONS

Where temperatures less than 5°C or greater than 35°C are encountered, contact our Technical Staff for specific advice.

This product is classified as non- hazardous under Worksafe guidelines, but should still be handled with due care. Any contact with eyes or skin should be washed off with clean soapy water. Protective gloves and clothing should be worn.

#### NOTE

Material safety data sheets for these and all Aftek products are available on request. Read the MSDS and product label carefully before using.

All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

#### ALLIED PRODUCTS

Aftek manufactures a broad range of construction products including.

Grouts	Coatings
Admixtures	Adhesives
Sealants	Floor Toppings
Floor Levelling Compounds	Concrete Repair

### MARKETING SERVICES

THOMSON WHITE AUST P/L  
250 Princes Hwy Dandenong Vic 3175  
Tel: (03) 9791 8211  
Fax: (03) 9791 8644  
Email: [ask@thomsonwhite.com.au](mailto:ask@thomsonwhite.com.au)