

Waterproofer

Economical water resisting admixture for concrete and masonry

DESCRIPTION

Integral water resisting admixture for concrete and masonry, above or below ground. Recommended for use where coloured mortar or integral floor colours are used.

ADVANTAGES

Water Based

Economical

Improved mix workability

Improved Durability

Suitable for after trades

TYPICAL PROPERTIES

Specific Gravity @ 20°C 0.98 gm/ml

pH @ 20°C 9.5 - 10.5

APPLICATION INSTRUCTIONS

Preparation

All surfaces to be treated must be free of oil, grease or other contamination which may inhibit the bond of the render. Any loose concrete should be removed prior to application of any mortar or render containing Waterproofer.

Mixing

Waterproofer is suitable for application straight out of the container without prior mixing,

Application

Add the Waterproofer to the mix at the rate of one to four litres per 40 kg of Portland cement. Add the Waterproofer to the gauge water rather than directly to the mix wherever possible. Do not premix with any admixture, always add any other admixtures separately to the mix.

Curing

Mortars and renders modified with Waterproofer should be cured with either Curecon W or Curecon PW.

CLEAN UP

Clean all equipment with water immediately after use.

ESTIMATING

Packaging

Waterproofer is supplied in 20 Litre plastic containers or 200 litre drums.

Approximate Material Usage

One to two litres per 40kg of Portland cement.

STORAGE

Waterproofer is an water based product which must be stored in the original unopened containers.

PRECAUTIONS

Where temperatures less than 5°C or greater than 35°C are encountered, contact our Technical Staff for specific advice.

Any contact with eyes or skin should be washed off with soap and clean water. Do NOT use solvent. If swallowed seek immediate medical treatment.

Protective gloves, goggles and clothing should be worn.

Do not use lime in water resistant mixes containing Waterproofer.

Avoid excessive use of Waterproofer in doses greater than those recommended.

MARKETING SERVICES

THOMSON WHITE AUST P/L

250 Princes Hwy Dandenong Vic 3175

Tel: (03) 9791 8211

Fax: (03) 9791 8644

Email: ask@thomsonwhite.com.au

WATERPROOFER

NOTE

Material safety data sheets for these and all. Aftok products are available on request Read the MSDS and product label carefully before using.

All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

ALLIED PRODUCTS

Aftok manufactures a broad range of construction products including:

Grouts

Coatings

Admixtures

Adhesives

Sealants

Floor Toppings

Floor Levelling Compounds

Concrete Repair