

Galprene SB

Multi purpose adhesive/sealant

USES

Neoprene based, solvent borne multi purpose adhesive and sealant. Particularly suited for use as sealant in air conditioning duct work.

ADVANTAGES

Excellent adhesion to galvanised iron, steel, aluminium, brick, concrete, wood, fibre-cement board, plywood.

- Paintable
- Good flexibility
- Easily used by cartridge gun.

PROPERTIES

Appearance	Silver grey, tacky liquid.
Viscosity	100,000 - 200,000 CPS
Solids	Approx. 69%
Specific Gravity	Approx. 1.1

APPLICATION INSTRUCTIONS

All surfaces should be clean and dry. Metal surfaces should be de greased prior to application of Galprene SB.

Apply direct from the cartridge after cutting nozzle to allow required bead size.

STORAGE

18 months in original container when stored in a cool dry place.

PACKAGING

300 ml Cartridges.

PRECAUTIONS

Health and Safety

Galprene SB contains flammable solvents. Use only in well ventilated areas away from heat, sparks and naked flames.

Avoid contact with skin and eyes and avoid breathing vapours.

Warning: do not deliberately sniff any adhesive. Sniffing may harm or kill you.

If swallowed **DO NOT** induce vomiting - give a glass of water and contact a Doctor or Poisons Information Centre. If skin contact occurs, wash skin thoroughly. If in eyes, hold eyes open flood with water for at least 15 mins. and see a Doctor. If inhaled to excess, apply artificial respiration if breathing ceases.

Fire

AFTEK Galprene SB is highly flammable during application. Dry film is flame retardant

Flash Point less than 9 degrees C

NOTE

Materials Safety Data Sheets for these and all AFTEK Products are available on request. Read MSDS and product label carefully before using.

All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

MARKETING SERVICES

THOMSON WHITE AUST P/L
250 Princes Hwy Dandenong Vic 3175
Tel: (03) 9791 8211
Fax: (03) 9791 8644
Email: ask@thomsonwhite.com.au