

# Galseal WB

Multi purpose flexible Adhesive/Sealant

---

## USES

Specialty formulation for use as a sealant in air conditioning duct joint and metal lap joints.

## ADVANTAGES

Excellent adhesion to galvanised iron, steel, aluminium, brick and concrete, wood, fibre-cement board, plywood.

- Easy clean up Non toxic
- Paintable
- Non flammable

## PROPERTIES

Appearance	Grey thick easily gunnable paste
Viscosity	100,000 - 200,000 CPS
Solids	Approx. 68%

## APPLICATION INSTRUCTIONS

All surfaces should be clean and dry. Metal surfaces should be degreased prior to application of Galseal WB. Application temperature should be between 10 degrees and 35 degrees C.

Apply direct from the cartridge after cutting nozzle to allow required bead size. Join components then drill and pop rivet the lap joints. Leave at least for 48 hours at 20 degrees C before placing ducts into service.

## STORAGE

18 months in original containers when stored in a cool dry place.

## PACKAGING

300 ml cartridges.

## PRECAUTIONS

### Health and Safety

Galseal WB is non flammable and non toxic and is therefore safe to use. However normal precautions required when using sealants and adhesives should apply.

## NOTE

Material safety data sheets for these and all AFTEK products are available on request. Read MSDS and product labels carefully before using. All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

## MARKETING SERVICES

THOMSON WHITE AUST P/L  
250 Princes Hwy Dandenong Vic 3175  
Tel: (03) 9791 8211  
Fax: (03) 9791 8644  
Email: [ask@thomsonwhite.com.au](mailto:ask@thomsonwhite.com.au)