

Presseal

Preformed flexible sealant.

USES

For use as a compression seal in lapjoints in roofing profiles, internal partition panels, precast concrete units, flange joints in ductwork, glazing and ductwork.

ADVANTAGES

- Ready and easy to use.
- Quick application
- Quick and easy clean up
- Dimensionally stable
- Paintable

PROPERTIES

Appearance	Preformed Grey or Black Sealant
Solids content	100%
Service Temp	- 20° C to + 50° C
Chemical Resistance	Resistant to dilute mineral acids or alkalis. Not resistant to organic solvents or oils.

APPLICATION INSTRUCTIONS

All surfaces should be clean dry and free of any grease or oil. Lay Presseal continually along one joint face and lightly press to achieve adhesion. Do not stretch Presseal.

Porous substrates may require priming prior to application Presseal can be applied in layers if a thicker section is required.

STORAGE

18 months in a cool dry place.

PACKAGING

Packed in reels in variety of widths and thicknesses.

Standard sizes

10 mm x 1.5 mm

12mm x 3mm

25mm x 3mm

6 mm Dia.

12 mm Dia.

PRECAUTIONS

Health and Safety

Generally non hazardous in normal application or use.

NOTE

Material safety data sheets for these and all Aftek Products are available on request. Read MSDS and product label carefully before using. All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

MARKETING SERVICES

THOMSON WHITE AUST P/L
250 Princes Hwy Dandenong Vic 3175
Tel: (03) 9791 8211
Fax: (03) 9791 8644
Email: ask@thomsonwhite.com.au